

# Data Digger Equipment

568 K/240 Krishnapalli, Alambagh, Lucknow. PIN 226005

GST: 09AFEPB9198K1ZW Website: <a href="www.datadigger.co.in">www.datadigger.co.in</a> E-mail: <a href="mailto:info@datadigger.co.in">info@datadigger.co.in</a>

Contact: +91-7880650032, +91-7505751181

# REFLECTIVE TARGETS

MODEL DDE10001A/10001B Series



#### **OVERVIEW**

Data Digger Equipment reflective targets are designed to suit a wide variety of surveying applications. They are used extensively for measurement of deformation during tunneling and subway construction, for monitoring bridges, dams, slopes and building structures.

#### **FEATURES**

- Precise, rugged, interchangeable and low cost.
- Compact construction.
- Easy installation.
- Robust frame and bolts with firm grip.
- Precise surveying application where total stations are used.

#### **APPLICATION**

- Measurement of deformation in tunnel.
- Measurement of deformation in subway construction.
- Monitoring of dams, bridges and slopes.
- Monitoring of building structures.
- Surveying works.









# Data Digger Equipment

568 K/240 Krishnapalli, Alambagh, Lucknow. PIN 226005

GST: 09AFEPB9198K1ZW Website: <a href="www.datadigger.co.in">www.datadigger.co.in</a> E-mail: <a href="info@datadigger.co.in">info@datadigger.co.in</a>

Contact: +91-7880650032, +91-7505751181

Material

Material

Break-off point 8 mm

### **DESCRIPTION**

## Model DDE-10001A Bi-flex target

Model DDE-10001A Bi-flex target consists of reflector mounted on a robust frame. The target has reflectors on both the sides and is mounted on a universal joint such that it can be oriented in any direction as required. The target has a small center hole to allow precise targeting.



The Bi-flex target is made of high performance materials and precise manufacturing processes. The target is thus, interchangeable.

### **Model DDE-10001B Prism target**

Model ERT-10P prism target consist of a mini prism mounted on a robust frame. This is also mounted on a universal joint such that it can be oriented in any direction as required. The target is interchangeable.



### **Optional components**

The optional components which can be ordered separately with both model DDE-10001A and DDE-10001B include convergence bolts with protective cap and adaptor with reference break-off point. The break-off point adaptor is required to mount the target on the convergence bolts.









## **SPECIFICATIONS**

DDE-10001A Bi-flex targe	et
Measuring range	Approximately 12 m to 140 m
Manufacturing	
accuracy	± 0.1 mm
	Reflector support is plastic,
	mounted on universal joints
Material	with reflective foil on both sides
DDE-10001B Prism targe	t
Measuring range	Approximately 0.3 m to 600 m
Manufacturing accuracy	± 0.1 mm
Addition Constant	+17.5 mm
Material	Prism support is plastic,
Material	mounted on universal joints
Protective cap	
Material	Red polyvinyl chloride
Break-off point 12 mm	

Plastic - Acetal

Plastic - Acetal